

Main

Range	PowerLogic
Product name	PowerLogic ENERGY METER
Product or component type	Energy meter
Device application	Energy monitoring

Complementary

Type of measurement	Energy consumption Power Peak demand power Reactive power Power factor Voltage Current
Measurement accuracy	+/- 1 %
Measurement voltage	120 V AC between phase and neutral 240 V AC between phases
[Us] rated supply voltage	120 V AC - 25...10 %
Network frequency	60 Hz 50 Hz
Line Rated Current	200 A
Display type	Backlit LCD
Display size	1.2 x 3.8 inch
Information displayed	Energy consumption Power Power maximum) Reactive power Power factor Voltage Current
Sampling rate	1280 Hz
Provided equipment	2 x current transformer
CT size	0.75 x 1.10 inch
Standards	ANSI C12.1
Product certifications	UL UL 3111-1 CUL
Maximum Width	7.60 in (193 mm)
Depth	Meter 2.99 in (76 mm)
Maximum Height	8.31 in (211 mm)

Environment

Isolation voltage	, 2500 V
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	32...122 °F (0...50 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	09779 - POWERLOGIC ENERGY METER
Discount Schedule	PL1
GTIN	00785901539322
Package weight(Lbs)	4.9 lb(US) (2.22 kg)
Returnability	No
Country of origin	US

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------