



Main

Product	Mechanically Held Lighting Contactor
Type	PB
Control Circuit	Common control circuit

Complementary

Control Circuit Voltage	240/277 V AC 60 Hz
Line Rated Current	150 A
Number of Poles	3P
AWG gauge	350 kcmil aluminium/copper)power AWG 18...AWG 10 copper)control
Maximum Overall Voltage	600 V AC
Auxiliary contact composition	Without
Mounting support	busbar
Electrical connection	Busbar connection
Maximum Height	9.49 in (241 mm)
Maximum Depth	3.39 in (86 mm)
Maximum Width	7.52 in (191 mm)

Environment

Product certifications	UL Listed CSA
------------------------	------------------

Ordering and shipping details

Category	21323 - 8903 PB
Discount Schedule	CP1
GTIN	00785901663447
Package weight(Lbs)	25 lb(US) (11.34 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------