Product data sheet Characteristics

GS1AM110

Auxiliary contacts, TeSys GS, 1 NO, early break, front mounting, for GS2 with front/side handle



Main

Range of product	TeSys
Device short name	GS1AM
Product or component type	Auxiliary contact
Contact application	O, I and test position signalling
Range compatibility	TeSys GS fuse-switch disconnector FuPact GS fuse-switch disconnector
Contacts type and composition	1 NO
Contact operation	Early-break
[Ith] conventional free air thermal current	10 A 104 °F (40 °C)
[le] rated operational current	6 A 120 V AC-15 3 A 240 V AC-15 1.8 A 400 V AC-15 1.5 A 480 V AC-15 2.8 A 24 V DC-13 1.4 A 48 V DC-13 0.55 A 125 V DC-13 0.27 A 250 V DC-13 0.15 A 400 V DC-13

Complementary

Mechanical durability	5 Mcycles	
Electrical durability	1 Mcycles AC-15	
Switch rated current	30 A	
	32 A	
	50 A	
	60 A	
	63 A	
	100 A	
	125 A	
	160 A	
	200 A	
	250 A	
	315 A	
	400 A	
	600 A	
	630 A	
	800 A	
	1250 A	
Fuse type	NFC	
	DIN	
	BS	
	CC	
	J	
Type of operating handle	External frontal	
	External right side	
	External left side	
Mounting location	Front face	
Net Weight	0.03 lb(US) (0.015 kg)	

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	l11
GTIN	00785901367741
Nbr. of units in pkg.	1
Package weight(Lbs)	0.03 lb(US) (0.01 kg)
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.79 in (2 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	3.54 in (9 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	40
Package 2 Weight	26.74 oz (758 g)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration

Contractual warranty

Warranty 1	18 months
------------	-----------