

Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	208 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	18 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	2 momentary push-buttons (START-STOP)
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	0
Maximum Height	12.28 in (312 mm)
Maximum Depth	7.13 in (181 mm)
Maximum Width	8.86 in (225 mm)

Environment

Enclosure Type	NEMA 3R painted sheet steel
Product certifications	CSA UL Listed NEMA

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	25.13 lb(US) (11.40 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
-------------------	---------------

Contractual warranty

Warranty	18 months
----------	-----------