

ZBW040D49

red light block for head Ø22 for BA9s bulb
230...240V screw terminal for lugs



Main

Range of product	Harmony XB4 Harmony XB5
Product or component type	Light block
Device short name	ZBW
Connections - terminals	Screw terminals for lug
Signalling type	Steady
Light source	LED
Bulb base	BA 9s
Light block supply	Integrated transformer 6 V
Light source colour	Red
[Us] rated supply voltage	230...240 V AC 50/60 Hz

Complementary

Supply voltage limits	195...264 V AC
Current consumption	14 mA
Service life	100000 h at rated voltage and 25 °C
Surge withstand	1 kV IEC 61000-4-5

Environment

Protective treatment	TH
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
IP degree of protection	IP20 IEC 60529
Standards	EN/IEC 60947-1 UL 508 EN/IEC 60947-5-5 EN/IEC 60947-5-4 CSA C22.2 No 14 EN/IEC 60947-5-1 JIS C8201-5-1 JIS C8201-1
Resistance to fast transients	2 kV IEC 61000-4-4
Resistance to electromagnetic fields	9.14 V/m (10 V/m) IEC 61000-4-3
Resistance to electrostatic discharge	6 kV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2
Electromagnetic emission	Class B IEC 55011

Ordering and shipping details

GTIN	03389110178470
Package weight(Lbs)	0.29 lb(US) (0.131 kg)

Packing Units

Package 1 Height	0.880 dm
Package 1 width	0.340 dm
Package 1 Length	0.540 dm

Contractual warranty

Warranty	18 months
----------	-----------