

Main

Body type	Sealed assembled body
Number of tap-offs	4 2.5 % FCBN
Product or component type	Dry Sealed Transformer

Complementary

Device application	Heating and lighting equipment Power circuit application
Enclosure material	Painted steel
Enclosure type	Weatherproof enclosure indoor/outdoor
Mounting support	wall
Phase	3 phase
Primary voltage	480 V delta AC
Rated power in VA	45 kVA
Secondary voltage	240 V delta AC
Temperature rise	115 °C

Environment

Environmental characteristic	Weatherproof
Insulation temperature	356 °F (180 °C)
NEMA degree of protection	NEMA 3R
Product certifications	CULus

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
Package weight(Lbs)	163.29 kg (360 lb(US))
Returnability	No

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.