



Main

| | |
|----------------------------|---|
| Range of product | OsiSense XC |
| Series name | Special format |
| Product or component type | Limit switch lever |
| Device short name | ZC2J |
| Product compatibility | XC2J |
| Associated head | ZC2JE03 ZC2JE04 ZC2JE05 ZC2JE06 ZC2JE02 ZC2JE07 ZC2JE01 |
| Movement of operating head | Rotary |
| Type of operator | Roller lever spring return metal offset) |
| Type of approach | Lateral approach |

Complementary

| | |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | Without |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) standard environment -40...158 °F (-40...70 °C) low temperature |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) standard environment -40...158 °F (-40...70 °C) low temperature |
| Environmental characteristic | Standard environment Low temperature Corrosive |

Ordering and shipping details

| | |
|-----------------------|------------------------------------|
| Category | 22449 - LIMIT SWITCHES,ACCESSORIES |
| Discount Schedule | T |
| GTIN | 03389110323061 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.8 lb(US) (0.36 kg) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 0.98 in (2.5 cm) |
| Package 1 width | 2.76 in (7 cm) |
| Package 1 Length | 2.76 in (7 cm) |

Offer Sustainability

| | |
|---------------------------|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|