

## Product data sheet

### Characteristics

## P620KA0B0R

ION6200 card - include RS485 PML+Modbus,  
2 SS pulse output, all measurement



### Main

Range	PowerLogic
Device short name	P620K
Product or component type	Option
Range compatibility	PowerLogic ION6200 ION6200 energy and power quality meter

### Complementary

Type of measurement	Current Voltage Frequency Harmonic distortion (I THD & U THD) Active and reactive power total Apparent power total Power factor Active and reactive energy Apparent energy Demand current (I1, I2, I3, Ig) Active and reactive power per phase Apparent power per phase
Number of outputs	2 form A triac output
Communication port protocol	Modbus RTU PML
Communication port support	RS485
Tamperproof of settings	Protected by access code
Mounting support	Slot

### Ordering and shipping details

Category	09751 - POWERLOGIC ION 6200 HARDWARE
Discount Schedule	PM1
Package weight(Lbs)	0.01 lb(US) (0.00 kg)
Returnability	Yes

### Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended to be used for determining the suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.