8538SCA11V08

NEMA Combination Starter, Type S, nonfusible disconnect, Size 1, 27A, 10 HP at 600 VAC polyphase, 208 VAC coil, NEMA 12



Main

Product	Combination Starter
Туре	S
Control Circuit Type	Common control circuit

Complementary

Starter Type Non reversing Number of Poles 3P Horsepower Rating 7.5 Hp 200 V AC, 3 phase 7.5 Hp 230 V AC, 3 phase 10 Hp 460 V AC, 3 phase 10 hp 575 V AC, 3 phase 10 hp 575 V AC, 3 phase Maximum Voltage Rating 600 V AC Control Units No control units Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch NEMA size 1	Control Circuit Voltage	208 V AC 60 Hz	
Horsepower Rating 7.5 Hp 200 V AC, 3 phase 7.5 Hp 230 V AC, 3 phase 10 Hp 460 V AC, 3 phase 10 hp 575 V AC, 3 phase Maximum Voltage Rating 600 V AC Control Units No control units Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Starter Type	Non reversing	 -
7.5 Hp 230 V AC, 3 phase 10 Hp 460 V AC, 3 phase 10 hp 575 V AC, 3 phase Maximum Voltage Rating 600 V AC Control Units No control units Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Number of Poles	3P	
Control Units Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Horsepower Rating	7.5 Hp 230 V AC, 3 phase 10 Hp 460 V AC, 3 phase	
Pilot Light No indicator Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Maximum Voltage Rating	600 V AC	
Auxiliary Contacts Without Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Control Units	No control units	
Thermal overload type Melting alloy 3 Disconnect Type Non-fusible disconnect switch	Pilot Light	No indicator	
Disconnect Type Non-fusible disconnect switch	Auxiliary Contacts	Without	
	Thermal overload type	Melting alloy 3	
NEMA size 1	Disconnect Type	Non-fusible disconnect switch	
	NEMA size	1	

Environment

Enclosure Type	NEMA 12 painted sheet steel without external reset

Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
Nbr. of units in pkg.	1
Package weight(Lbs)	40 lb(US) (18.14 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Under investigation

Contractual warranty

Warranty	18 months