



Main

Product or component type	Tap box
Range of product	Powerbus

Complementary

Current Rating	400 A
Busbar Configuration	5A L1 + IG + L2 + N + L3
Busbar Material	Silver plated copper busbar
Integral Ground	50 percent capacity integral ground bus
Voltage Rating	600 V AC
Number of Phases	3 phase
Wiring configuration	4-wire (isolated ground and 100 percent neutral)
Wire Gauge	AWG 1...600 kcmil 2 phase and neutral AWG 10...AWG 2/0 2 ground
Enclosure material	Painted aluminium Black


Environment

IP degree of protection	IP40
-------------------------	------

Ordering and shipping details

Category	20171-NEW 100A & 225A POWERBUS
Discount Schedule	PE8
Package weight(Lbs)	95.00 lb(US) (43.091 kg)
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information