8736SCO4V08

Reversing Starter Size 1, 3-Pole, Melting Alloy Overload, Horizontal Open



Main

Product	Starter
Туре	S
Control Circuit Type	Common control circuit

Complementary

Complementary		
Control Circuit Voltage	208 V AC 60 Hz	
Starter Type	Reversing	
Motor type	Repulsion induction	
Number of Poles	3P	
Phase	1 phase	
Motor Wiring	4 wires	
Current Rating	27 A	
Horsepower Rating	3 HP 230 V AC 2 HP 115 V AC	
Maximum Voltage Rating	600 V AC	
Control Units	No control units	
Thermal overload type	Melting alloy 3	
Electrical connection	Screw clamp terminals	
NEMA size	1	
Maximum Height	6.93 in (176 mm)	
Maximum Depth	5.31 in (135 mm)	
Maximum Width	7.13 in (181 mm)	

Environment

Enclosure Type	Not rated (open device)
Orientation	Horizontal
Product certifications	NEMA UL Listed CSA

Ordering and shipping details

Category	21272 - 8702,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	7.65 lb(US) (3.47 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months