

ATV660U22U3

variable speed drive ATV660 - 2.2kW/3HP -
230 V

Main

Range of product	Altivar 660 Drive System
Product or component type	Variable speed drive
Product specific application	Process and utilities
Device short name	ATV600
Product destination	Synchronous motors Asynchronous motors
Mounting mode	Wall-mounted
Function available	Customised provided equipment Customised option card Customised enclosure colour Customised cable entry
Maximum Horse Power Rating	3 hp
Cable entry	Top Bottom
Colour of enclosure	Light grey RAL 7035)
IP degree of protection	IP23 UL 508 A IP54
Degree of protection	UL type 1 UL type 12 UL type 3R
Type of cooling	Forced convection
[Us] rated supply voltage	230 V + 10 % - 15 %
Supply frequency	50/60 Hz +/- 5 %
Phase	3 phase
Overvoltage category	III
Asynchronous motor control profile	Optimized torque mode Variable torque standard Constant torque standard
Permissible temporary current boost	1.1 x In 60 s normal duty) 1.5 x In 60 s heavy duty)
Nominal switching frequency	2.5 kHz
Switching frequency	0.5...8 kHz adjustable
Motor power kW	2.2 kW
Maximum THDI	<48 % full load IEEE 519
Energy efficiency ratio	0.95

Environment

Pollution degree	2 IEC 60664-1
Vibration resistance	1.5 mm peak to peak 3...13 Hz)IEC 60721-3-3
Relative humidity	95 % without condensation or dripping water IEC 60068-2-78
Ambient air temperature for operation	14...104 °F (-10...40 °C)
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Operating altitude	3280.84 ft (1000 m) without
Standards	UL 508 A

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.