# Product data sheet Characteristics

## 8538SCW11S8V06

NEMA Combination Starter, Type S, nonfusible disconnect, Size 1, 27A, 10 HP at 600 VAC polyphase, 480 VAC coil, NEMA 4X

#### Main

Contactor application	Non-reversing
Device short name	S

### Complementary

Maximum Depth	8.34 in (211.84 mm)	
Device mounting	Surface	
Maximum Height	24.06 in (611.12 mm)	
NEMA size	1	
Number of poles	3	
Number of thermal units required	3	
Net Weight	40 lb(US) (18.14 kg)	
Maximum Width	9.5 in (241.30 mm)	

#### Environment

NEMA degree of protection	NEMA 4/4X
Product certifications	CSA LR584 class 3211 04 UL listed file E152395 CCN NKJH7

#### Ordering and shipping details

0 11 0		
Category	21218 - 8538,39 W/STAINLESS ENCLOS	
Discount Schedule	CP1	
Nbr. of units in pkg.	1	
Package weight(Lbs)	45 lb(US) (20.41 kg)	
Returnability	No	
Country of origin	MX	

#### Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

#### Contractual warranty

oontractaan mananty		
Warranty	18 months	