



Main

Network rated voltage	600 V AC 60 Hz
Reactive power rating	150 kvar
Operating mode	Automatic
Range of product	VarSet
Device short name	VarSet standard
Product or component type	Capacitor bank
Controller type	Varplus Logic VPL6 Modbus
Capacitor technology	VarPlus Can
Accessibility for operation	Front
Color	Gray RAL 7035)

Complementary

Network pollution level	No polluted
[THDv] Total Harmonic Distortion	0...3 %
Power per step	25 kvar
Step composition	2x25 + 2x50
Location of connection	Top
Internal voltage transformer	600/120 V
Poles description	3P
Capacitance tolerance	- 5 % to 10 %
Maximum permissible voltage	1.1 x Un 8 hours over 24 hours)
Protection type	Circuit breaker protection
Breaking capacity	50 kA
Control type	Rotary handle
Maximum weight	275.58 Lb(US) (125 kg) 275 lb(US) (124.74 kg)
Height	47.24 In (1200 mm) 47.2 in (1198.88 mm)
Width	39.37 In (1000 mm) 39.4 in (1000.76 mm)
Maximum Depth	15.75 In (400 mm) 15.7 in (398.78 mm)
Mounting location	Indoor

Environment

Standards	CSA C22.2 No 190-M1985 UL 810
NEMA degree of protection	NEMA 1
Mechanical degree of protection	IK10
Relative humidity	0...95 %
Operating altitude	<= 6561.68 ft (2000 m)
Ambient air temperature for operation	14...104 °F (-10...40 °C)
Average ambient air temperature for operation	30 °C annual)

Ordering and shipping details

Category	00085 - VARSET VLV LV CAP BANK (CTO)
Discount Schedule	DE2C
Package weight(Lbs)	150 lb(US) (68.04 kg)
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information