Product data sheet Characteristics

9001KP7W6

round pilot light \varnothing 30 - white - incandescent BA 9s - 220/240 V AC - IP66





Main

Range of product	Harmony 9001K
Product or component type	Pilot light
Device short name	9001K

Complementary

Complementary		
Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Shape of signaling unit head	Round	
Lens type	Domed glass	
Cap/operator or lens colour	White	
Light source	incandescent	
Bulb base	BA 9s	
Light block supply	Via integral transformer 220240 V AC 50/60 Hz 6 V)	
Connections - terminals	Screw clamp terminals, 1 x 0.222 x 1.5 mm² IEC 60947-1	
Tightening torque	7.08 lbf.in (0.8 N.m) IEC 60947-1	
Shape of screw head	Cross slotted	
Operating position	Any position	
[Ui] rated insulation voltage	250 V 2)IEC 60947-1	
[Uimp] rated impulse withstand voltage	2.5 kV IEC 60947-1	
Short-circuit protection	10 A cartridge fuse IEC 60947-5-1	
[Ith] conventional free air thermal current	10 A	
CAD overall width	2.13 in (54 mm)	
CAD overall height	2.76 in (70 mm)	
CAD overall depth	1.65 in (42 mm)	
[Us] rated supply voltage	220240 V AC	
Net Weight	0.46 lb(US) (0.21 kg)	
Device presentation	Complete product	

Environment

Standards	CSA C22.2 No 14 EN/IEC 60947-1 JIS C 852 EN/IEC 60947-5-4 UL 508 EN/IEC 60947-5-1 JIS C8201-5-1 JIS C8201-1
Product certifications	NEMA UL 508
Protective treatment	TC
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27
Overvoltage category	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6

Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
Package weight(Lbs)	0.5 lb(US) (0.23 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months	