



## Main

|                                 |                                      |
|---------------------------------|--------------------------------------|
| Range of product                | Harmony XB5                          |
| Product or component type       | Head for non-illuminated push-button |
| Device short name               | ZB5                                  |
| Product compatibility           | Legend holder                        |
| Bezel material                  | Dark grey plastic                    |
| Mounting diameter               | 0.87 in (22 mm)                      |
| Head type                       | Standard                             |
| Sale per indivisible quantity   | 1                                    |
| Shape of signaling unit head    | Round                                |
| Type of operator                | Spring return                        |
| Operator profile                | Red flush, unmarked                  |
| Operator additional information | Coloured boot                        |

## Complementary

|                             |                                                                                                                                                                                                |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width           | 1.18 in (30 mm)                                                                                                                                                                                |
| CAD overall height          | 1.18 in (30 mm)                                                                                                                                                                                |
| CAD overall depth           | 1.30 in (33 mm)                                                                                                                                                                                |
| Net Weight                  | 0.05 lb(US) (0.021 kg)                                                                                                                                                                         |
| Mechanical durability       | 10000000 cycles                                                                                                                                                                                |
| Station name                | XALD 1...5 cut-outs<br>XALK 2...5 cut-outs                                                                                                                                                     |
| Electrical composition code | C1 9 single front mounting<br>C2 9 single and double front mounting<br>C11 3 single front mounting<br>C15 1 single front mounting<br>SF1 3 single front mounting<br>SR1 3 single rear mounting |
| Device presentation         | Basic element                                                                                                                                                                                  |

## Environment

|                                       |                                                                       |
|---------------------------------------|-----------------------------------------------------------------------|
| Protective treatment                  | TH                                                                    |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                            |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)                                            |
| Overvoltage category                  | Class II IEC 60536                                                    |
| IP degree of protection               | IP66 IEC 60529<br>IP67 IEC 60529<br>IP69 IEC 60529<br>IP69K ISO 20653 |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                                    |
| Resistance to high pressure washer    | 1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m                         |
| IK degree of protection               | IK03 IEC 50102                                                        |

|                        |                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------|
| Standards              | UL 508<br>CSA C22.2 No 14<br>JIS C8201-5-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>JIS C8201-1 |
| Product certifications | GL<br>UL Listed<br>CSA<br>LROS (Lloyds register of shipping)<br>BV<br>DNV<br>RINA                                   |
| Shock resistance       | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms) half sine wave acceleration IEC 60068-2-27  |
| Vibration resistance   | 5 gn 2...500 Hz)IEC 60068-2-6                                                                                       |

## Ordering and shipping details

|                       |                                       |
|-----------------------|---------------------------------------|
| Category              | 22467 - PUSHBUTTONS,22MM(PLASTIC) NEW |
| Discount Schedule     | CS2                                   |
| GTIN                  | 00785901356417                        |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 0.04 lb(US) (0.02 kg)                 |
| Returnability         | No                                    |
| Country of origin     | FR                                    |

## Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Package 1 Height       | 1.85 in (4.7 cm) |
| Package 1 width        | 1.38 in (3.5 cm) |
| Package 1 Length       | 2.20 in (5.6 cm) |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                          |
| REACH free of SVHC         | Yes                                                                                            |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                  |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                        |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|