

Micro Data Center for IT Environments

S-SERIES

Made for server rooms or network closets, our S-Series is highly customizable and easy to configure with hardware, software, and services, including validation of third party IT equipment with all the largest vendors. For full catalogue, ask your partner to visit designportal.apc.com to access the Local Edge Configurator.



	Wall Mounted Enclosures	Standard Enclosures	Self-Contained System w/ Cooling
Enclosure			
Enclosure Size H x W x D (mm)	355-620 x 600 x 400 or 600	1200-2258 x 600/750/800 x 1070-1200	2000 x 900/1050 x 1500 2000 x 600 x 1200
Enclosure Size H x W x D (in)	14-24 x 24 x 16 or 24	48-90 x 24/30/32 x 42-48	80 x 36/42 x 60
Total Rack Space	6U, 9U, 12U	12U, 18U, 24U, 42U, 45U, 48U	42U
Available Rack U Space	Configuration Dependent	Configuration Dependent	37U 32U (with InRack Cooling)
Power			
Maximum IT Load	Configuration Dependent	Configuration Dependent	4.6kW 3.5kW (with InRack Cooling)
UPS Capacity	500VA-1.5kW	1 – 20kVA	5kVA
UPS Runtime*	Configuration Dependent	Configuration Dependent	3.5min
Power Input	120V, 230V	120V, 208V, 230V	208V, 230V
Cooling			
Cooling Capacity	N/A	N/A	5kW (InRow SC) 3.5kW (InRack Cooling)
Cooling Type	Vented Enclosure	Perforated Doors	InRow SC (Self-Contained, DX) Uniflair RM (Split DX, InRack)
Security			
Security Options	Standard Lock, Keycard Access, Camera Monitoring	Standard Lock, Keycard Access, Camera Monitoring	Standard Lock, Keycard Access, Camera Monitoring
Environmental Sensing Options	Temp/Humid, Spot Water, Rope Leak, Intrusion Detection, Smoke, Vibration		
Remote Monitoring	EcoStruxure IT Remote Monitoring (Phone App, Web)		
Ship Load-able?	No	Yes (Shock Pkg)	Yes (Shock Pkg – Rack Only)

* Battery Packs available for additional runtime