Product data sheet Characteristics

XKDF1435666

joystick controller +options



Main

Range of product	Harmony XK
Product or component type	Complete joystick controller
Product specific application	Medium hoisting applications
Device short name	XKD
Sale per indivisible quantity	1

Complementary

Bezel material	Metal
Fixing collar material	Metal
Protective treatment	TC
Operator position information	All positions
Operator profile	Dead man's handle, 1 NC + 1 NO, slow-break
Positive opening	Slow break, double-break with
Connections - terminals	Captive screw clamp terminals, <= 2 x 1.5 mm ² with cable end Captive screw clamp terminals, <= 1 x 2.5 mm ² without cable end Captive screw clamp terminals, >= 1 x 0.5 mm ²
Short-circuit protection	10 A cartridge fuse gG EN/IEC 60947-5-1
[Ith] conventional free air thermal current	10 A EN/IEC 60947-5-1 10 A CSA C22.2 No 14
[Ui] rated insulation voltage	500 V 3)IEC 60947-1

Environment

Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-4158 °F (-2070 °C)	
Overvoltage category	Class I IEC 61140	
Standards	EN/IEC 60947-5-1 CSA C22.2 No 14	
Mechanical durability	3000000 cycles	
Vibration resistance	2 gn 10500 Hz)IEC 60068-2-6	
Shock resistance	15 gn 11 ms) IEC 60068-2-27	

Ordering and shipping details

22474 - PUSHBUTTON, CRANE JOYSTICKS
1
00785901850045
4.93 lb(US) (2.24 kg)
No
FR

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lea compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	☑ China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months