

### Main

|                                  |                                                    |
|----------------------------------|----------------------------------------------------|
| Product                          | Combination Starter                                |
| Type                             | S                                                  |
| Control Circuit Type             | Separate control circuit                           |
| Control Units                    | No control units                                   |
| Enclosure Type                   | NEMA 4/4X stainless steel with external reset      |
| Auxiliary Contacts               | Without                                            |
| Horsepower Rating                | 10 Hp 460 V AC, 3 phase<br>10 hp 575 V AC, 3 phase |
| Number of Poles                  | 3P                                                 |
| Maximum Voltage Rating           | 600 V AC                                           |
| NEMA Size                        | 1                                                  |
| Control Circuit Voltage          | 110 V AC 50 Hz<br>120 V AC 60 Hz                   |
| Pilot Light                      | No indicator                                       |
| Starter Type                     | Reversing                                          |
| Overload Type                    | Melting alloy                                      |
| Number of Thermal Units Required | 3                                                  |
| Disconnect Type                  | Fusible disconnect R, 30 A                         |

### Ordering and shipping details

|                     |                                    |
|---------------------|------------------------------------|
| Category            | 21297 - 8738,39 W/STAINLESS ENCLOS |
| Discount Schedule   | CP1                                |
| Package weight(Lbs) | 57 lb(US) (25.85 kg)               |
| Returnability       | No                                 |
| Country of origin   | MX                                 |

### Offer Sustainability

|                   |                                          |
|-------------------|------------------------------------------|
| EU RoHS Directive | Will be compliant – Date to be confirmed |
|-------------------|------------------------------------------|

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|