

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE CERTIFICATS D'ESSAIS DES EQUIPEMENTS ELECTRIQUES (IECEE) METHODE OC

**CB TEST CERTIFICATE    CERTIFICAT D'ESSAI OC**

Product  
Produit

Uninterruptible power supply

Name and address of the applicant  
Nom et adresse du demandeur

American Power Conversion Corp.  
85 Rangeway Road Building #2, NORTH BILLERICA MA 01862  
UNITED STATES OF AMERICA

Name and address of the manufacturer  
Nom et adresse du fabricant

American Power Conversion Corp.  
85 Rangeway Road Building #2, NORTH BILLERICA MA 01862  
UNITED STATES OF AMERICA

Name and address of the factory  
Nom et adresse de l'usine

APC India Pvt. Ltd.  
187/3, 188 Jigani Village Jigani Hobli, 562106 BANGALORE  
INDIA

Note: When more than one factory, please report on page 2  
Note: Lorsque il y plus d'une usine, veuillez utiliser la 2<sup>ème</sup> page

Ratings and principal characteristics  
Valeurs nominales et caractéristiques principales

Additional Information on page 2  
Input: AC 200-240 V; max. 30 A; 50-60 Hz  
Output: AC 200-240 V; max. 30 A; 50-60 Hz, max. 4500W  
(see Model Matrix)

Trademark (if any)  
Marque de fabrique (si elle existe)



Type of Manufacturer's Testing Laboratories used  
Type de programme du laboratoire d'essais constructeur

TMP

Model / Type Ref.  
Ref. De type

see Model Matrix

Additional information (if necessary may also be reported on page 2)  
Les informations complémentaires (si nécessaire, peuvent être indiqués sur la 2<sup>ème</sup> page)

Class I

Additional Information on page 2

A sample of the product was tested and found to be in conformity with  
Un échantillon de ce produit a été essayé et a été considéré conforme à la

IEC 62040-1(ed.1);corrigendum1

As shown in the Test Report Ref. No. which forms part of this Certificate  
Comme indiqué dans le Rapport d'essais numéro de référence qui constitue partie de ce Certificat

1924400-3335-0035/191140

This CB Test Certificate is issued by the National Certification Body  
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**

**VDE** Prüf- und Zertifizierungsinstitut GmbH  
**VDE** Testing and Certification Institute  
Zertifizierungsstelle / Certification



Date: 2013-11-21

Signature:

E. Biehl

Elcoteq Electronics, (India) Pvt., Ltd. Block No. VIII, Velankani Information Systems Campus #43 Electronics City, Phase II, Hosur Road, 560100 BANGALORE INDIA	APC (India) PVT LTD No. 18(A), Survey 128, Jigani Village & Hobli Anekal, Taluk, 562106 BANGALORE INDIA
East India Packagings Pvt. Ltd. (Electronic Division) Survey No 17, Kammanahalli Bannerghata Road, 560076 BANGALORE INDIA	APC (India) PVT LTD Jigani Village & Hobli Premise 4, No. 73 Survey 103, ANEKAL, TALUK, 562106 BANGALORE INDIA
APC (Xiamen) Power Infrastructure Co. Ltd. 1678 JiXian Road, TongAn District, 361100 XIAMEN CITY CHINA	

**Additional information (if necessary)**  
**Information complémentaire (si nécessaire)**

**VDE** Prüf- und Zertifizierungsinstitut GmbH  
**VDE** Testing and Certification Institute  
Zertifizierungsstelle / Certification

Date: 2013-11-21

Signature:



E. Biehl

CB Certificate: DE1-43132/A4  
File Ref.: 1924400-335-0035

MODEL MATRIX

W W W W W X X X X X Y Y Y Y Y Y Y Z Z Z Z Z Z

W W W W W = MANUFACTURERS PREFIX A TO Z (may take up to 5 characters)  
Low Voltage Isolated Secondary Differences Only(Non-Safety Critical)

X X X X X = VA OUTPUT 0 TO 9 (may take up to 5 characters)  
See Current VA Levels below:

2200, 3000, 5000, 6000

Y Y Y Y Y Y Y Y = UNIT CONFIGURATION A TO Z and/or 0 to 9 (may take up to 10 alphanumeric characters)

Current UPS Configurations : I = International, R or RM = Rack Mount, XL = Extended Run, U = Unit Height,  
NET = Software in shipping box, PS = Power Switch, B = Black Bezel, BP = Battery Pack, DR = Din Rail Mount

Z Z Z Z Z Z = X followed by up to a three digit number 0 to 9(may take up to 6 characters)[Non safety critical difference only]

**Example of how to use Matrix:** SURT        3000   XLI  
  WWWW    XXXXX YYYYYYYYY

ZZZZZZ

**Product Voltages (all units):** 200VAC-240VAC

**Product Frequency (all units):** 50/60Hz

**Maximum Input Current:**     30 A

**Present Model Prefixes Example:** SURT, SMRT, IBM, EMC,SURTD

**Example of Models Covered by Matrix:**

SURTD2200XLIM, SURT3000XLI-ET, SURTD3000RMXLI, SURTD3000XLI, SURTD3000XLIM, SURTD5000RMXLI, SURTD5000XLI, SURTD5000XLI-ET, SURT6000RMXLI, SURT6000XLI, SURT6000XLI-ET, SURT6000XLIM, DLRTD3000RMXLI3U and DLRTD5000RMXLI3U