



Main

Audible noise at 1 meter from surface of unit	74 dBA
Ambient air temperature for operation	-4...122 °F (-20...50 °C)
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Maximum Depth	29.61 in (75.2 cm)
Maximum Height	8.58 in (21.8 cm)
Nominal Input Voltage	200...240 V
Mounting mode	Not rack-mountable
Mounting preference	No preference
Input Frequency	60 Hz
Product certifications	UL Listed
Net Weight	57.32 lb(US) (26 kg)
Provided equipment	120/240V power supply Built-in modbus protocol adapter
Maximum Width	18.66 in (47.4 cm)
Number of Power Feeds	1
Number of rack unit	5U
Ambient air temperature for storage	-4...122 °F (-20...50 °C)
Relative humidity	20...80 %

Ordering and shipping details

Package weight(Lbs)	66.14 lb(US) (30 kg)
---------------------	----------------------

Packing Units

Package 1 Height	12.99 in (33 cm)
Package 1 width	22.83 in (58 cm)
Package 1 Length	37.40 in (95 cm)

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.