



### Overview

Presentation	UPS management SmartSlot Card with Dry Contact (relay) support to monitor external triggers and initiate actions on external devices.
Lead time	Usually in Stock

### General

Provided equipment	User Manual USB cable
--------------------	--------------------------

### Physical

Color	Black
Maximum Depth	4.49 in (11.4 cm)
Maximum Height	1.50 in (3.8 cm)
Net Weight	0.46 lb(US) (0.21 kg)
Maximum Width	4.76 in (12.1 cm)

### Conformance

Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-6 FCC Part 15 class A
-----------	---

### Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)


### Ordering and shipping details

Category	09305 - INDUSTRIAL UPS
GTIN	00731304293842
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	PH

## Packing Units

Package 1 Height	2.01 in (5.1 cm)
Package 1 width	9.25 in (23.5 cm)
Package 1 Length	6.26 in (15.9 cm)
Number of Units in Package 3	896

## Offer Sustainability

EU RoHS Directive	Under investigation
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------