



## Main

Product or component type	Plug-in unit
Range of product	I-Line
Circuit breaker type	H-frame
Trip unit technology	Thermal-magnetic

## Complementary

Protection type	Circuit breaker
Mounting mode	Plug-in
[Ue] rated operational voltage	600 V AC
Line Rated Current	110 A
Number of Phases	3 phase
Poles description	3P
Interrupt Rating	100 KA 240 V AC 65 KA 480 V AC 25 kA 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Wiring configuration	3-wire (integral ground bus)
AWG gauge	AWG 8...AWG 3/0 1 phase and neutral AWG 6...AWG 2/0 1 ground
Maximum Depth	9.13 in (232 mm)
Maximum Height	8.50 in (216 mm)
Maximum Width	21.69 in (551 mm)

## Environment

Product certifications	CSA C22.2 No 27 UL listed file E22182
Standards	UL 857

## Ordering and shipping details

Category	20183-PFH /PHG/PHJ/ PHL C/B PLUGS
Discount Schedule	PE7
Package weight(Lbs)	32.00 lb(US) (14.515 kg)
Returnability	No

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------