



Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	270 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Solid state Motor Logic class 10/20
Electrical connection	Screw clamp terminals
NEMA size	5
Maximum Height	44.21 in (1123 mm)
Maximum Depth	12.95 in (329 mm)
Maximum Width	17.20 in (437 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	NEMA UL Listed CSA

Ordering and shipping details

Category	21194 - 8502,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
Package weight(Lbs)	150 lb(US) (68.04 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------