

8538SCASP6

NEMA Combination Starter, Type S, 30A
fusible disconnect, Size 1, 27A, Motor Logic
SSOLR, 120 VAC coil, NEMA 3R/12



Main

Product	Combination Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Non reversing
Line Rated Current	27 A
Number of Poles	3P
Horsepower Rating	10 Hp 460 V AC, 3 phase 10 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO)
Pilot Light	Red indicator on LED Green indicator off LED
Auxiliary Contacts	2 NO + 2 NC
Thermal overload type	Solid state Motor Logic class 10/20 6...18 A
Disconnect Type	Fusible disconnect switch H and K, 30 A, electrical SPD
NEMA size	1
Maximum Height	24 in (609.60 mm)
Maximum Depth	8.34 in (211.84 mm)
Maximum Width	9.5 in (241.30 mm)

Environment

Enclosure Type	NEMA 12 painted sheet steel with external reset
Product certifications	CSA UL Listed

Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901875543
Nbr. of units in pkg.	1
Package weight(Lbs)	38.94 lb(US) (17.66 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	10.80 in (27.432 cm)
Package 1 width	13.10 in (33.274 cm)
Package 1 Length	29.10 in (73.914 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	18 months
----------	-----------