ZB5AK1483

yellow illuminated selector switch head Ø22 2-position spring return



Main Range of product Harmony XB5 Product or component Head for illuminated selector switch type Product compatibility Integral LED ZB5 Device short name Bezel material Dark grey plastic Mounting diameter 0.87 in (22 mm) Sale per indivisible quantity Shape of signaling unit Round head

Right to left spring return

Yellow standard handle

2 positions 90°

\sim				
Col	mp	lem	ien	tarv

CAD overall width	1.14 in (29 mm)	
CAD overall height	1.14 in (29 mm)	
CAD overall depth	1.69 in (43 mm)	
Net Weight	0.04 lb(US) (0.017 kg)	
Mechanical durability	1000000 cycles	
Station name	XALD 15 cut-outs XALK 25 cut-outs	
Electrical composition code	M3 4 single front mounting integral LED M6 2 single front mounting integral LED and transformer M10 2 single front mounting integral LED MF1 2 single front mounting integral LED MR1 2 single rear mounting integral LED M4 4 single and double front mounting integral LED	
Device presentation	Basic element	

Type of operator

Operator profile

information

Operator position

Environment

LITVITOTITICITE		
Protective treatment	TH	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
Overvoltage category	Class II IEC 60536	
IP degree of protection	IP66 IEC 60529 IP67 IP69 IP69K	
NEMA degree of protection	NEMA 13 NEMA 4X	
Resistance to high pressure washer	1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m	
IK degree of protection	IK06 IEC 50102	
Standards	UL 508 JIS C8201-5-1 EN/IEC 60947-5-5 CSA C22.2 No 14 EN/IEC 60947-5-4 EN/IEC 60947-1 EN/IEC 60947-5-1 JIS C8201-1	

Product certifications	RINA	
	BV	
	DNV	
	CSA	
	GL	
	UL Listed	
	LROS (Lloyds register of shipping)	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27	
	50 gn 11 ms) half sine wave acceleration IEC 60068-2-27	

Ordering and shipping details

GTIN	03606481206251
Package weight(Lbs)	0.04 lb(US) (0.016 kg)

Packing Units

Package 1 Height	0.480 dm
Package 1 width	0.330 dm
Package 1 Length	0.520 dm

Offer Sustainability

Oner Sustamability	
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information