



Main

Product	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Reversing
Number of Poles	3P
Phase	3 phase
Current Rating	45 A
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	2
Maximum Height	14.13 in (359 mm)
Maximum Depth	7.68 in (195 mm)
Maximum Width	14.88 in (378 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	CSA NEMA UL Listed

Ordering and shipping details

Category	21272 - 8702,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901455646
Nbr. of units in pkg.	1
Package weight(Lbs)	30.85 lb(US) (13.99 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	10.00 in (25.400 cm)
Package 1 width	15.60 in (39.624 cm)
Package 1 Length	16.60 in (42.164 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------