## ZB5AD2C0

black selector switch head 2 pos stay put cp grey



## Main

Harmony XALF Harmony XB5
Head for selector switch
ZB5
Plastic colour plated grey
0.87 in (22 mm)
Standard
1
Round
Stay put
Black standard handle
2 positions 90°

## Complementary

Device presentation	Basic element
	SR1 3 single rear mounting
	SF1 3 single front mounting
	C15 1 single front mounting
	C11 3 single front mounting
	C8 4 single and double front mounting
Licotrical composition code	C7 4 single front mounting
	C6 5 single and double front mounting
	C5 5 single front mounting
	C4 6 single and double front mounting
Electrical composition code	C3 6 single front mounting
	XALK 25 cut-outs
Station name	XALD 15 cut-outs
Mechanical durability	1000000 cycles
Net Weight	0.04 lb(US) (0.017 kg)
CAD overall depth	1.81 in (46 mm)
CAD overall height	1.14 in (29 mm)
	· ,
CAD overall width	1.14 in (29 mm)

## **Environment**

Protective treatment	TH	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
Overvoltage category	Class II IEC 60536	
IP degree of protection	IP67 IEC 60529	
NEMA degree of protection	NEMA 13 NEMA 4X	
Resistance to high pressure washer	1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m	
IK degree of protection	IK06 IEC 50102	

Standards	JIS C8201-5-1
Ciandards	CSA C22.2 No 14
	UL 508
	EN/IEC 60947-1
	EN/IEC 60947-5-4
	EN/IEC 60947-5-1
	JIS C8201-1
Product certifications	GL
	CSA BV
	DNV
	RINA
	LROS (Lloyds register of shipping)
	UL Listed
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27
	50 gn 11 ms) half sine wave acceleration IEC 60068-2-27
Package weight(Lbs)	0.85 oz (24.000 g)
Packing Units	
	1.65 in (4.200 cm)
Package 1 Height	1.65 in (4.200 cm) 1.30 in (3.300 cm)
Packing Units Package 1 Height Package 1 width Package 1 Length	
Package 1 Height Package 1 width Package 1 Length	1.30 in (3.300 cm)
Package 1 Height Package 1 width Package 1 Length  Offer Sustainability	1.30 in (3.300 cm) 2.05 in (5.200 cm)
Package 1 Height Package 1 width Package 1 Length  Offer Sustainability REACh free of SVHC	1.30 in (3.300 cm) 2.05 in (5.200 cm)  Yes
Package 1 Height Package 1 width Package 1 Length  Offer Sustainability REACh free of SVHC	1.30 in (3.300 cm) 2.05 in (5.200 cm)
Package 1 Height Package 1 width Package 1 Length  Offer Sustainability REACh free of SVHC EU RoHS Directive	1.30 in (3.300 cm)  2.05 in (5.200 cm)  Yes  Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS
Package 1 Height Package 1 width Package 1 Length  Offer Sustainability	1.30 in (3.300 cm)  2.05 in (5.200 cm)  Yes  Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Package 1 Height Package 1 width Package 1 Length  Offer Sustainability REACh free of SVHC EU RoHS Directive  Toxic heavy metal free	1.30 in (3.300 cm)  2.05 in (5.200 cm)  Yes  Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration Yes
Package 1 Height Package 1 width Package 1 Length  Offer Sustainability REACh free of SVHC EU RoHS Directive  Toxic heavy metal free Mercury free	1.30 in (3.300 cm)  2.05 in (5.200 cm)  Yes  Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration  Yes Yes