

## Product data sheet

### Characteristics

## 2510KW2CH

Switch, manual, 30A, 3 pole, 10 HP at 575 VAC, three phase, toggle operated, red 440/600 VAC indicator, NEMA 4 enclosure



### Main

|         |                           |
|---------|---------------------------|
| Product | Single Unit Manual Switch |
| Type    | K                         |

### Complementary

|                        |                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Current Rating         | 30 A                                                                                                                     |
| Cable Entry            | 0.75 NPT (top and bottom)                                                                                                |
| Horsepower Rating      | 2 Hp 115 V AC<br>1 Hp 90 V DC<br>2 Hp 115 V DC<br>1.5 Hp 230 V DC<br>7.5 Hp 230 V AC<br>10 Hp 460 V AC<br>10 hp 575 V AC |
| Maximum Voltage Rating | 600 V AC<br>230 V DC                                                                                                     |
| Number of Poles        | 3P                                                                                                                       |
| Control Unit Type      | Toggle                                                                                                                   |
| Number of Phases       | 3 phase                                                                                                                  |
| Pilot Light            | Red indicator, 440...600 V                                                                                               |
| Starter Type           | Non reversing                                                                                                            |
| Electrical Connection  | Screw clamp terminals                                                                                                    |
| Wire Gauge             | AWG 14...AWG 10 copper                                                                                                   |
| Maximum Height         | 4.38 in (111.25 mm)                                                                                                      |
| Maximum Width          | 3 in (76.20 mm)                                                                                                          |
| Maximum Depth          | 4.56 in (115.82 mm)                                                                                                      |

### Environment

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Certifications        | UL listed file E42243 CCN NLRV<br>CSA LR25490 class 3211 05 |
| NEMA Enclosure Rating | NEMA 4 die cast zinc alloy standard size                    |

### Ordering and shipping details

|                     |                          |
|---------------------|--------------------------|
| Category            | 21102 - 2510,2511,2512 K |
| Discount Schedule   | CP1                      |
| GTIN                | 00785901376415           |
| Package weight(Lbs) | 3.01 lb(US) (1.37 kg)    |
| Returnability       | No                       |
| Country of origin   | MX                       |

Offer Sustainability

|                       |                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation      |  <a href="#">REACH Declaration</a>      |
| REACH free of SVHC    | Yes                                                                                                                      |
| EU RoHS Directive     | Not compliant                                                                                                            |
| China RoHS Regulation |  <a href="#">China RoHS Declaration</a> |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|