

PFMIEC090D1N11C

All In One Module 90kW 11rack InRow DX
480V



Main

Battery curve	A
Battery Volt-Amp-Hour Capacity	0 VAh
Battery type	VRLA
Bypass type	Internal Bypass (Automatic and Manual)
Color	White
Cooling option	Air-cooled Split System
Crest factor	Unlimited
Maximum Depth	539.37 in (1370 cm)
Maximum Height	142.83 in (362.8 cm)
Number of input connectors	1 Hard Wire 4-wire (3PH + G)
Nominal Input Voltage	3 phase
Efficiency at full load	408...552 V adjustable 480 V 408...552 V 480 V
Liquid Electrolyte Value	0
Mounting mode	Not rack-mountable
Input Frequency	60 Hz +/- 0.5 / 1 / 2 / 4 / 6 / 8 % programmable
Included Battery Modules	0
Battery Slots Empty	0
Number of power module filled slots	0
Number of power module free slots	0
Rack Free Space	462
Number of racks	11
Number of rack unit	42U
Number of tare power	0 W
PDU Amp Capacity	16 A
PDU Type	Metered
KW per Rack	8.1 W
Product certifications	CUL Listed UL Listed
Net Weight	59300.01 lb(US) (26898.01 kg)
Provided equipment	EcoStruxure IT ready (UPS) Integrated network management
Kw Rating	90000 W
Configured Power	90000 W
UPS size	WS
Waveform Type	Sine wave
Maximum Width	153.94 in (391 cm)
Ambient air temperature for operation	-13...104 °F (-25...40 °C)
Operating altitude	0...1500 ft
IP degree of protection	IP55
Output voltage	208 V 3 phase
Product web sub-family	All-in-one modules

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Output

Output Frequency (sync to mains)	60 Hz sync to mains
----------------------------------	---------------------

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------
