



Main

Product	Sealed Transformer
Certifications	UL Listed
Type	Mini Power-Zone
Enclosure Code	A
Insulation Temperature	365 °F (185 °C)
Phase	1 phase
Primary Voltage	480 V
Secondary Voltage	120/240 V
Full Capacity Taps	2 5 % FCBN
Power Rating	5 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Circuit Breaker Type	Primary main breaker Secondary main breaker Feeder breaker
Interior Type	QO Load Center interior
Number of Spaces Available	10
Number of Circuits	10
Enclosure Type	NEMA 3R hot-rolled steel

Complementary

Height	32.7 in (830.58 mm)
Width	12 in (304.80 mm)
Depth	11.9 in (302.26 mm)
Product Weight	135.00 lb(US) (61.235 kg)

Ordering and shipping details

Category	16275 - MPZ PLUG ON BRANCH CB
Discount Schedule	PE2
GTIN	00785901838944
Package weight(Lbs)	139 lb(US) (63.05 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions



