



Main

Product range	Legacy
Product type	Socket
Product compatibility	Relay 788XBXR/XCXR
Number of terminals	11
Switch function	3PDT
Contact composition	3 NO + 3 NC

Complementary

Line Rated Current	15 A
Rated voltage	300 V
Contact terminal arrangement	Mixed
Connections - terminals	Output screw clamp terminalssolid Output screw clamp terminalsstranded
Tightening torque	Chassis 0.8 N.m, AWG 14...AWG 12, copper Screw < 1 N.m Screw < 0.8 N.m
Fixing mode	By screw M3.5, M3.5 panel By screws, M3 panel
Shape of screw head	Combination roundhead
Net Weight	1.80 oz (51 g)
Width	141.08 ft (43.00 m)
Depth	2.24 in (57 mm)


Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
Flame retardance	UL94-V0
Product certifications	UL CSA CE RoHS

Ordering and shipping details

GTIN	03606480277955
------	----------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.