



Main

Range	PratiKa
Product or component type	Interlocked socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

Complementary

Line Rated Current	125 A
[Ue] rated operational voltage	380...415 V
Network frequency	50/60 Hz
Protection type	Residual current breaker with overcurrent protection (RCBO)
Plug, socket material	Housing self-extinguishing engineering polymer
Connections - terminals	Captive screws
Cable cross section	0.02...0.15 in ² (16...95 mm ²)
Cable entry	Cable gland
Thread type	Pg 42
Net Weight	24.47 lb(US) (11.1 kg)
Maximum Height	27.95 in (710 mm)
Maximum Width	10.63 in (270 mm)
Maximum Depth	8.46 in (215 mm)
Color	Gray RAL 7035)
Voltage colour	Red

Environment

Standards	EN 60309-2 EN 60309-1
IP degree of protection	IP65 IEC 60529
IK degree of protection	IK08 EN 62262
Fire resistance	1760 °F (960 °C) IEC 60695-2-11
Relative humidity	50 % 104 °F (40 °C) 70 % 86 °F (30 °C) 90 % 68 °F (20 °C)
Ambient air temperature for operation	95 °F (35 °C) 86400 s)

Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	00785901430018
Nbr. of units in pkg.	1
Package weight(Lbs)	95 lb(US) (43.09 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.42 in (29 cm)
Package 1 width	10.63 in (27 cm)
Package 1 Length	27.56 in (70 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------