



### Overview

Lead time	Usually in Stock
-----------	------------------



### General

Provided equipment	Mounting Hardware Rack Mounting brackets Serial configuration cable
--------------------	---------------------------------------------------------------------------

### Physical

Cable length	8 ft (2.44 m)
Color	Black
Maximum Depth	9.29 in (23.6 cm)
Maximum Height	3.46 in (8.8 cm)
Net Weight	13.96 lb(US) (6.33 kg)
Maximum Width	17.01 in (43.2 cm)

### Input

Input Frequency	50/60 Hz
Line Rated Current	24 A
Plug standard	NEMA L5-30P
Max line current	30 A
Input current limits	30 A
Load Capacity	2880 VA
Nominal Input Voltage	120 V

### Output

Maximum Total Current Draw per Phase	30 A
Number of power socket outlets	16 NEMA 5-20R
Protection type	Circuit breaker
Output voltage	120 V

### Conformance

Standards	EN 55022 Class A FCC Part 15 class A
-----------	-----------------------------------------

## Environmental

Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)


## Ordering and shipping details

GTIN	00731304333524
Package weight(Lbs)	19.44 lb(US) (8.82 kg)

## Packing Units

Package 1 Height	8.27 in (21 cm)
Package 1 width	22.99 in (58.4 cm)
Package 1 Length	14.02 in (35.6 cm)

## Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Under investigation
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------