



### Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

### Complementary

Control Circuit Voltage	550 V AC 50 Hz 600 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	135 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	4
Maximum Height	32.20 in (818 mm)
Maximum Depth	9.57 in (243 mm)
Maximum Width	18.15 in (461 mm)

### Environment

Enclosure Type	NEMA 4/4X brushed stainless steel
Product certifications	UL Listed CSA NEMA

### Ordering and shipping details

Category	21203 - 8502,36 W/STAINLESS ENCLOSURES
Discount Schedule	CP1
Package weight(Lbs)	67.38 lb(US) (30.56 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#"> China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------