



Main

| | |
|-------------------------------|--|
| Range | TeSys |
| Device short name | VZ |
| Product or component type | Auxiliary contact block |
| Performance level | High performance |
| Contacts type and composition | 1 NO + 1 NC |
| Contact operation | Late-make 1 NO Early-break 1 NC |
| Product compatibility | V2 V5 V02 V6 V1 V4 V01 V0 V3 |
| Network type | AC DC |
| Network frequency | 50/60 Hz |

Complementary

| | |
|--|---|
| Mounting location | Right |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ith] conventional free air thermal current | 12 A |
| [Ithe] conventional enclosed thermal current | 10 A |
| Mechanical durability | 100000 cycles |
| Electrical durability | 30000 Cycles DC-11 100000 cycles AC-15 |
| Connections - terminals | Screw clamp terminals 2 0.00...0.00 in ² (0.75...1.5 mm ²) flexible - with cable end Screw clamp terminals 2 0.00...0.00 in ² (1...2.5 mm ²) solid |
| Tightening torque | 6.20 lbf.in (0.7 N.m) screw clamp terminals |
| Maximum Height | 2.56 in (65 mm) |
| Maximum Width | 0.79 in (20 mm) |
| Maximum Depth | 1.91 in (48.5 mm) |
| Net Weight | 0.11 lb(US) (0.05 kg) |

Environment

| | |
|---------------------------------------|--------------------------------|
| Standards | IEC 60947-5 |
| Product certifications | GL CSA UL |
| Protective treatment | TC |
| IP degree of protection | IP20 IEC 60529 |
| Ambient air temperature for operation | -4...122 °F (-20...50 °C) |
| Fire resistance | 1760 °F (960 °C) IEC 60695-2-1 |

Ordering and shipping details

| | |
|-----------------------|------------------------|
| Category | 21730 - V VARIO SWITCH |
| Discount Schedule | CP1 |
| GTIN | 00785901305743 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.12 lb(US) (0.05 kg) |
| Returnability | Yes |
| Country of origin | CZ |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.46 in (3.7 cm) |
| Package 1 width | 2.17 in (5.5 cm) |
| Package 1 Length | 3.54 in (9 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 69 |
| Package 2 Weight | 8.90 lb(US) (4.035 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|