



Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--



General

Provided equipment	Installation guide Operations and maintenance manual
Compressor Type	Scroll
Air Discharge Patterns	Horizontal
Intake Air	Rear Return
Air flow	1088 ft³/min (513.48 l/s)
Piping Material	Copper
Fluid connection type	SWT

Physical

Color	White
Maximum Depth	41.30 in (104.9 cm)
Maximum Height	12.99 in (33 cm)
Net Weight	165.39 lb(US) (75.02 kg)
Maximum Width	37.40 in (95 cm)

Input

Minimum Circuit Amp Capacity	5 A
Input Frequency	60 Hz
Maximum Overcurrent Protection	15 A
Nominal Input Voltage	208 V 230 V

Conformance

Product certifications	ETL
------------------------	-----

Environmental

Operating altitude	0...2000 ft
--------------------	-------------

Communications & Management

Control panel	Multi-function LCD status and control console
---------------	---

Ordering and shipping details

Package weight(Lbs)	214.99 lb(US) (97.52 kg)
---------------------	--------------------------

Packing Units

Package 1 Height	21.69 in (55.1 cm)
Package 1 width	54.29 in (137.9 cm)
Package 1 Length	46.50 in (118.1 cm)