

Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	27 A
Number of Poles	4P
Number of Phases	2 phases
Horsepower Rating	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 2
Electrical connection	Screw clamp terminals
NEMA size	1
Maximum Height	12.13 in (308 mm)
Maximum Depth	7.05 in (179 mm)
Maximum Width	6.50 in (165 mm)


Environment

Enclosure Type	NEMA 4X glass polyester
Product certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21202 - 8502,36 S*R,S*T,S*W
Discount Schedule	CP1
Package weight(Lbs)	35.02 lb(US) (15.88 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Will be compliant – Date to be confirmed

Contractual warranty

Warranty	18 months
----------	-----------