



Main

Range of product	ConneXium
Product or component type	Ethernet TCP/IP managed switch
Concept	Transparent Ready
Communication port protocol	Ethernet TCP/IP SSH HTTP HTTPS SNMP MRP (Media Redundancy Protocol) RSTP SFTP SCP LLDP
Port Ethernet	100BASE-FX - 2 fiber optic 10BASE-T/100BASE-TX - 14 copper cable
Maximum number of switches in cascade	Unlimited
Cybersecurity	Port hardening Role-based access control

Complementary

Integrated connection type	Duplex SC fiber optic Shielded RJ45 copper cable
Transmission support medium	Twisted shielded pairs cable CAT 5E copper cable Multimode optical fiber fiber optic
Maximum cable distance between devices	328.08 ft (100 m) copper cable
Optic fiber length	2.49 mile (4 km) 62.2/125 µm
Attenuation	11 DB 62.2/125 µm) 8 dB 50/125 µm)
Ethernet service	Multicast filtering Configuration via web server IGMP Snooping SMTP V3 Data stream control VLAN Secure port SNMP-Traps and SYSLOG Priority port
Communication service	Telnet TFTP Address conflict detection Port monitoring Port mirroring
Diagnostics run time	Signal contact Self test
Maximum number of switches in a ring	50
Redundancy	Redundant single ring Ring coupling Redundant power supplies HiPER ring
[Us] rated supply voltage	24 V
Supply voltage limits	9.6...60 V DC SELV 18...30 V AC SELV
Power consumption in W	11.8 W
Electrical connection	Removable connector 6 ways power supply
Mounting support	35 mm symmetrical DIN rail

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Marking	CE
Local signalling	P1 P2 power supplies 2 LEDs Fault 1 LED Ring manager 1 LED Stand-by 1 LED Copper port activity 1 LED per channel Copper port status 1 LED per channel
Alarm output	1 voltfree contact 1 A
Alarm function	Switch fault Data link status Power supply fault Redundancy ring fault
Ethernet cabling system	TF switches
MTBF reliability	324619.0 H
Maximum Width	4.37 in (111 mm)
Maximum Height	5.16 in (131 mm)
Maximum Depth	4.37 in (111 mm)
Net Weight	1.32 lb(US) (0.6 kg)

Environment

Ambient air temperature for operation	32...140 °F (0...60 °C)
Relative humidity	10...95 % without condensation
IP degree of protection	IP20
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2012/19/EU - WEEE directive
Standards	CUL 60950 UL 1604 CSA C22.2 No 213 Class I Division 2 CSA C22.2 No 142 UL 508
Product certifications	GL C-tick

Ordering and shipping details

Category	18225 - PLC NTRK HRDWR & PROWORX SOFTWARE
Discount Schedule	PC41
GTIN	00785901471288
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.12 in (13 cm)
Package 1 width	6.30 in (16 cm)
Package 1 Length	9.45 in (24 cm)

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

