# **KAXZ1S139**

operating head with bezel  $\varnothing$  28.5 mm, metal - key Ronis other number



#### Main

Range of product	Harmony Series K
Product or component type	Cam switch operating head
Component name	KAX
Product compatibility	Front mounting bodies 12 and 20 A Ø 22 mm hole
Cam switch head type	With bezel Ø 28.5 mm, metal
Type of operator	Key Ronis other number
Rotary handle padlocking	Without
Presentation of legend	With mat black
Switching angle	30 °

### Complementary

Mechanical durability	1000000 cycles	
Net Weight	0.14 lb(US) (0.065 kg)	
Compatibility code	KAX	

#### Environment

Protective treatment	TC
Ambient air temperature for operation	-13131 °F (-2555 °C)
Ambient air temperature for storage	-40158 °F (-4070 °C)
Shock resistance	30 gn IEC 68-2-27
Vibration resistance	5 gn 10150 Hz)IEC 68-2-6
IP degree of protection	IP65 IEC 529 IP65 NF C 20-010

#### Ordering and shipping details

Category	21446 - 9003 K CAM SWITCHES
Discount Schedule	CS1
GTIN	03389110885835
Nbr. of units in pkg.	1
Package weight(Lbs)	0.14 lb(US) (0.06 kg)
Returnability	No

## Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	2.36 in (6 cm)	
Package 1 width	1.22 in (3.1 cm)	
Package 1 Length	1.22 in (3.1 cm)	

## Offer Sustainability

REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration

## Contractual warranty

Warranty 18	3 months
-------------	----------