



Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	18 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	Selector switch (HAND-OFF-AUTO)
Pilot Light	Red indicator on incandescent
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	0
Maximum Height	13.27 in (337 mm)
Maximum Depth	7.01 in (178 mm)
Maximum Width	10.98 in (279 mm)

Environment

Enclosure Type	NEMA 7/9 cast iron bolted
Product certifications	UL Listed NEMA CSA

Ordering and shipping details

Category	21202 - 8502,36 S*R,S*T,S*W
Discount Schedule	CP1
Package weight(Lbs)	50 lb(US) (22.68 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Will be compliant – Date to be confirmed
-------------------	--

Contractual warranty

Warranty	18 months
----------	-----------