



Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

General

Provided equipment	EcoStruxure IT ready (UPS)
--------------------	----------------------------

Physical

Color	White
Maximum Depth	238.50 in (605.8 cm)
Maximum Height	120.00 in (304.8 cm)
Net Weight	32959.14 lb(US) (14950 kg)
Number of racks	5
Rack Free Space	210
Number of rack unit	42U
Maximum Width	95.98 in (243.8 cm)

Input

Nominal Input Voltage	3 phase
-----------------------	---------

Output

Kw Rating	25000 W
Output Frequency (sync to mains)	60 Hz sync to mains
KW per Rack	7 kW
Output voltage	208 V 3 phase
PDU Type	Metered
Configured Power	25000 W

Conformance

Product certifications	UL Listed
------------------------	-----------

Environmental

Ambient air temperature for operation	5...113 °F (-15...45 °C)
Operating altitude	0...10000 ft
Storage altitude	0...10000 ft (0.00...3048.00 m)

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Battery type	VRLA
Liquid Electrolyte Value	0
Battery Volt-Amp-Hour Capacity	0 VAh

Communications & Management

Emergency Power Off (EPO)	Optional
---------------------------	----------

Ordering and shipping details

Package weight(Lbs)	33069.37 lb(US) (15000 kg)
---------------------	----------------------------

Packing Units

Package 1 Height	120.00 in (304.8 cm)
Package 1 width	95.98 in (243.8 cm)
Package 1 Length	238.50 in (605.8 cm)

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---