



Main

Product range	Legacy
Product type	Socket
Product compatibility	Relay 788XBXR/XCXR Suppressor module 70-ASMM Diode 70-ASMD Signalling device 70-ASMLG
Number of terminals	11
Switch function	3PDT
Contact composition	3 NO + 3 NC

Complementary

Line Rated Current	25 A
Rated voltage	300 V
Contact terminal arrangement	Separate
Connections - terminals	Output lift terminalssolid Output lift terminalsstranded
Tightening torque	Chassis 0.8 N.m, AWG 14...AWG 10, copper Screw 1 N.m
Fixing mode	Clip-on 35 mm symmetrical DIN rail
Net Weight	3.39 oz (96 g)
Width	1.42 in (36 mm)
Depth	2.24 in (57 mm)



Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
IP degree of protection	IP20
Flame retardance	UL94-V0
Product certifications	UL CSA CE RoHS

Ordering and shipping details

GTIN	03606480278198
------	----------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.