

Schneider Electric is further extending the superior features and performance of the NetShelter SX enclosure to Edge applications.



Schneider Electric is excited to announce the expansion of the flagship NetShelter SX enclosure line with the addition of 12U and 18U cabinet heights. These globally available server racks are ideal for storage of industry standard hardware including servers, voice, data and networking equipment required for Edge solutions.

The cabinet is compatible with a wide range of Schneider Electric UPSs, PDUs and with NetBotz; simply replace the standard swing handle with the NetBotz Rack Access swing handle. NetBotz provides the functionality required at the Edge including remote access, video capture, environmental monitoring with optional smoke and fluid detection. A complete solution can be configured for your edge applications in the Schneider Electric Local Edge Configurator. Schneider Electric's turn key solutions allow the cabinet to be deployed in remote locations with confidence and peace of mind.

All cabinets are UL2416 listed and are available with optional shock packaging. The shock packaging has been tested to International Safety Transit Association (ISTA) 3E shipping standards. The 12U has a dynamic weight capacity of 272 kg (600 pounds) while the 18U has a weight capacity of 408 kg (900 pounds) making it ideal for rack and stack roll outs for retail, medical and education. The 1070mm deep (42.1") cabinet also provides versatility to mount deep equipment at the point of compute in Edge applications.

Life Is On



Part Numbers

Part Number	U Space	Width	Depth	Static Weight Capacity	Dynamic Weight Capacity	Color
AR3003	12U	600mm (23.6")	900mm (35.42")	272kg (600 pounds)	272kg (600 pounds)	Black
AR3003SP	12U	600mm (23.6")	900mm (35.42")	272kg (600 pounds)	272kg (600 pounds)	Black
AR3103	12U	600mm (23.6")	1070mm (42.13")	272kg (600 pounds)	272kg (600 pounds)	Black
AR3103SP	12U	600mm (23.6")	1070mm (42.13")	272kg (600 pounds)	272kg (600 pounds)	Black
AR3006	18U	600mm (23.6")	900mm (35.42")	408kg (900 pounds)	408kg (900 pounds)	Black
AR3006SP	18U	600mm (23.6")	900mm (35.42")	408kg (900 pounds)	408kg (900 pounds)	Black
AR3106	18U	600mm (23.6")	1070mm (42.13")	408kg (900 pounds)	408kg (900 pounds)	Black
AR3106SP	18U	600mm (23.6")	1070mm (42.13")	408kg (900 pounds)	408kg (900 pounds)	Black

*SP denotes the unit is supplied with shock packaging

Feature

Standard swing handle
(upgradable to NetBotz Rack Access)

Field reversible door

UL2416 Listed

Shock Packaging (ISTA 3E tested)

Depth option of 42.13" (1070mm)

Bolt Down Bracket

Local Edge Configurator Availability

Benefit

High security handle with optional NetBotz upgrade option to provide remote access, increased security and environmental monitoring

Allows for mounting near an adjacent wall

Stated weight load verified by independent third party

Increase deployment speed while lowering field engineering costs

Ideal for mounting deep equipment at compute point

Secure the cabinet to the floor in high traffic environments

Configure a complete solution that meets your application requirements including UPS, PDU, NetBotz and EcoStruxure software



Technical Specifications

- Heights 12U, 18U
- Widths 600mm (23.6")
- Weight Capacities:
 - 12U - 272kg (600 pounds) static/dynamic
 - 18U - 408kg (900pounds), static/dynamic
- UL2416 Listed
- Shock Packaging (ISTA 3E tested)
- Casters and levelers included
- Cage nuts and screws included
- Bolt down bracket included
- Accessory channel included
- Color - Black
- Ships fully assembled
- Global Availability

Schneider Electric Industries SAS
35, rue Joseph Monier - CS 30323
F92506 Rueil-Malmaison Cedex

Life Is On

APC
by Schneider Electric