

# Product data sheet

## Characteristics

# LX4D7BD

TeSys D - contactor coil - LX4D7 - 24 V DC  
standard for 80 A contactor



### Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX4D7
Inductance of closed circuit	1.89 H
Product compatibility	LC1D80
Mechanical durability	10 Mcycles
Maximum operating rate	3600 cyc/h 140 °F (60 °C)

### Complementary

Coil technology	Without built-in suppressor module
Time constant	75 ms
Inrush power in W	22 W 68 °F (20 °C))
Hold-in power consumption in W	22 W 68 °F (20 °C)

### Environment

Ambient air temperature for operation	23...140 °F (-5...60 °C)
Net Weight	1.50 lb(US) (0.68 kg)

### Ordering and shipping details

Category	22341 - CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	00785901209911
Nbr. of units in pkg.	1
Package weight(Lbs)	1.36 lb(US) (0.62 kg)
Returnability	No
Country of origin	CZ

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.15 in (8 cm)
Package 1 width	3.35 in (8.5 cm)
Package 1 Length	4.92 in (12.5 cm)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide which is known to the State of California to cause Carcinogen harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
---------------------------	---

### Contractual warranty

Warranty	18 months
----------	-----------