



Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	90 A
Number of Poles	2P
Number of Phases	2 phases
Horsepower Rating	15 HP 230 V AC 7.5 HP 115 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 2
Electrical connection	Screw clamp terminals
NEMA size	3
Maximum Height	31.50 in (800 mm)
Maximum Depth	9.57 in (243 mm)
Maximum Width	18.15 in (461 mm)



Environment

Enclosure Type	NEMA 12 painted sheet steel
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901662365
Package weight(Lbs)	29.43 lb(US) (13.35 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------