



Overview

Presentation	Feature-rich enclosure specifically for the professional A/V market and optimized for cable management, power distribution, and airflow management.
Lead time	Usually in Stock

General

Provided equipment	Baying hardware Documentation CD Installation guide Leveling feet Mounting Hardware Pre-installed casters
--------------------	--

Physical

Maximum Mounting Depth	26.73 in (67.89 cm)
Number of rack unit	42U
Color	Black
Maximum Depth	31.73 in (80.6 cm)
Rack Width	19"
Maximum Height	78.39 in (199.1 cm)
Net Weight	151.33 lb(US) (68.64 kg)
Permanent permissible load	2250 Lb(US) (1020.58 kg) dynamic 3000 lb(US) (1360.78 kg) static
Maximum Width	23.62 in (60 cm)

Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------



Ordering and shipping details

GTIN	00731304284123
Package weight(Lbs)	182.39 lb(US) (82.73 kg)

Packing Units

Package 1 Height	83.50 in (212.1 cm)
Package 1 width	29.49 in (74.9 cm)
Package 1 Length	40.51 in (102.9 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------