



Overview

Presentation	The Rack Fan Tray is a low cost solution that aids in heat removal from a Netshelter Enclosure. The system easily installs into the top of the enclosure and expels heat from the roof of the rack. Wall-mounted enclosures have the additional option of installing the rack fan tray systems in the base of the rack as well. The fan trays are designed to promote bottom to top airflow within the enclosure.
Lead time	Usually in Stock

General

Provided equipment	Installation guide 1 x IEC to NEMA 5-15P power cord 2 x Fans
--------------------	--

Physical

Color	Black
Maximum Depth	6.89 in (17.5 cm)
Maximum Height	2.13 in (5.4 cm)
Net Weight	4.01 lb(US) (1.82 kg)
Maximum Width	12.52 in (31.8 cm)

Input

Input Frequency	50/60 Hz
Nominal Input Voltage	120 V
Plug standard	NEMA 5-15P

Conformance

Product certifications	CSA UL Listed
------------------------	------------------

Ordering and shipping details



GTIN	00731304225201
Package weight(Lbs)	6.02 lb(US) (2.73 kg)

Packing Units

Package 1 Height	2.56 in (6.5 cm)
Package 1 width	13.15 in (33.4 cm)
Package 1 Length	9.37 in (23.8 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------