



Main

Range	TeSys
Product name	TeSys Integral 63
Product or component type	Contactor breaker
Device short name	LD4LD

Complementary

Utilisation category	AC-43 AC-1
Poles description	3P
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Ie] rated operational current	63 A AC AC-1 63 A AC AC-43
[Ith] conventional free air thermal current	63 A 104 °F (40 °C)
Motor power kW	15 KW 220...240 V AC 50/60 Hz 30 KW 400 V AC 50/60 Hz 33 KW 415 V AC 50/60 Hz 37 KW 500 V AC 50/60 Hz 55 KW 660 V AC 50/60 Hz 33 kW 440 V AC 50/60 Hz
[Uc] control circuit voltage	24 V DC
Test function	Self test
Control type	Knob emergency stop Red front CNOMO
Irms rated making capacity	756 A IEC 60947-4 946 A IEC 60947-4
[Ipk] rated peak withstand current	105 kA IEC 60947-2
Breaking capacity	Icu 10 kA 600...690 V 0.5) IEC 60947-2 Icu 30 kA 480...525 V 0.25) IEC 60947-6-2 Icu 50 kA <= 440 V 0.25) IEC 60947-2
[Ics] rated service breaking capacity	10 KA 600...690 V IEC 60947-2 35 KA 480...525 V IEC 60947-2 50 kA <= 440 V IEC 60947-2
Maximum breaking time	4 ms
Thermal stress limit	300000 A².s
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-4
Control circuit voltage limits	0.25...0.7 Uc drop-out 131 °F (55 °C) 0.85...1.1 Uc operation 131 °F (55 °C)
[Ui] rated insulation voltage	690 V IEC 60947-1
Inrush power in W	300 W 68 °F (20 °C))
Hold-in power consumption in W	8 W 68 °F (20 °C)
Heat dissipation	5 W 32 A per pole, hot state power circuit 7 W 50 A per pole, hot state power circuit 9 W 63 A per pole, hot state power circuit 4.4 W 25 A per pole, hot state power circuit 5.8 W 40 A per pole, hot state power circuit
Operating time	15...25 ms DC opening 68 °F (20 °C) control circuit 25...40 ms DC closing 68 °F (20 °C) control circuit

Electrical durability	1 Mcycles AC-3 3 kA 415 V - after 1 cycle O-CO-r-CO at Isc 0.9 Mcycles AC-3 10 kA 415 V - after 1 cycle O-CO-r-CO at Isc 0.6 Mcycles AC-3 25 kA 415 V - after 1 cycle O-CO-r-CO at Isc 0.5 Mcycles AC-3 35 kA 415 V - after 1 cycle O-CO-r-CO at Isc 0.2 Mcycles AC-3 50 kA 415 V - after 1 cycle O-CO-r-CO at Isc
Mechanical durability	1.2 Mcycles
Connections - terminals	Power circuit screw clamp terminals 1 0.01...0.08 in ² (6...50 mm ²) flexible - without cable end Power circuit screw clamp terminals 2 0.01...0.04 in ² (6...25 mm ²) flexible - without cable end Power circuit screw clamp terminals 1 0.01...0.04 in ² (6...25 mm ²) flexible - with cable end Power circuit screw clamp terminals 2 0.01...0.04 in ² (6...25 mm ²) flexible - with cable end Power circuit screw clamp terminals 1 0.01...0.08 in ² (6...50 mm ²) solid
Tightening torque	Power circuit 53.10 lbf.in (6 N.m) screw clamp terminals
Width	3.54 in (90 mm)
Maximum Height	9.57 in (243 mm)
Depth	7.56 in (192 mm)
Net weight	8.38 lb(US) (3.8 kg)

Environment

Standards	NF C 20-040 IEC 60947-4 NF C 63-130 NEN VDE 0110 VDE 0660 BS 5424 IEC 60364 IEC 60158-1 NF C 63-650 IEC 60947-1 VDE 0113 IEC 60947-2 VDE 0170 BS 4941 IEC 60204-2 NF C 63-110 IEC 60204-1 VDE 0171 NF C 63-120 NBN VDE 0100 VDE 471 NF C 79-100 BS 4752
Product certifications	ASEFA NKK LROS (Lloyds register of shipping) GL SCC ASE DNV BV SETI DEMKO OVE USSR RINA ASTA CSA NEMKO UL
Protective treatment	TH
Ambient air temperature for operation	-4...140 °F (-20...60 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)
Mechanical robustness	Vibrations de-energised3 Gn, 1...300 Hz Vibrations energised3 Gn, 1...300 Hz Shocks de-energised8 Gn for 11 ms Shocks energised8 Gn for 11 ms

IP degree of protection	IP20 B IEC 60144 IP20 B IEC 60529
Operating altitude	9842.52 ft (3000 m) without derating

Ordering and shipping details

Category	22382 - STRS,INTEGRAL 32&63,OPEN
Discount Schedule	I11
GTIN	00785901920045
Nbr. of units in pkg.	1
Package weight(Lbs)	9.74 lb(US) (4.42 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.06 in (23 cm)
Package 1 width	5.71 in (14.5 cm)
Package 1 Length	12.20 in (31 cm)

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------