



Main

Range of product	Multi 9
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[Uc] control circuit voltage	110...415 V AC 50/60 Hz 110...130 V DC
9 mm pitches	2

Complementary

Range compatibility	Multi 9 C60 Multi 9 ID Multi 9 N40
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Maximum Height	3.25 in (82.5 mm)
Maximum Width	0.71 in (18 mm)
Maximum Depth	2.68 in (68 mm)
Connections - terminals	Clamp terminal - 1 0.00 in ² (2.5 mm ²) - flexible
Wire stripping length	0.35 in (9 mm)
Tightening torque	8.85 lbf.in (1 N.m)

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA KEMA ASTA LCIE
Tropicalisation	2 EN/IEC 60947-5-1
Relative humidity	95 % 131 °F (55 °C)
Ambient air temperature for operation	-13...122 °F (-25...50 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	01078 - DE2 MISC
Discount Schedule	DE2
GTIN	00785901421238
Nbr. of units in pkg.	1
Package weight(Lbs)	0.8 lb(US) (0.36 kg)
Returnability	No
Country of origin	BE

Packing Units

Package 1 Height	0.900 dm
Package 1 width	0.300 dm
Package 1 Length	0.800 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------